

IN THE CLAIMS:

Please cancel Claims 1-7 and add new Claims 8-26, as follows:

AMENDMENTS TO THE CLAIMS:

1-7 (cancelled)

8. (New) A baking oven, comprising:

a baking chamber;

a baking rack insertable in said baking chamber;

a holding part, said holding part horizontally guided
in said baking chamber;

said holding part receiving and holding said baking
rack;

said holding part and said baking rack displaceable
between a baking position with said baking rack inside said
baking chamber and a removed position with said baking rack
located, at least in part, outside and in front of said
baking chamber; and

said holding part including two retaining elements
arranged on opposite side walls of said baking chamber and
at a distance from at least one of the top wall and the
bottom wall of said baking chamber.

9. (New) The baking oven according to claim 8, including
each of said two retaining elements is guided by a
displaceable carriage.

10. (New) The baking oven according to claim 9, including
each said displaceable carriage is arranged one of said
opposite side walls of said baking chamber in a middle
height region of said baking chamber.

11. (New) The baking oven according to claim 9, including each of said two retaining elements including a hooked rail which is affixed to one of said displaceable carriages.

12. (New) The baking oven according to claim 11, including said hooked rails are coupled to one another by a cross bracing.

13. (New) The baking oven according to claim 9, including each of said displaceable carriages includes a locating position at least in said removed position.

14. (New) The baking oven according to claim 9, including each of said displaceable carriages is roller-mounted on a guide rail.

15. (New) The baking oven according to claim 14, including a forward and a rear stop position on at least one of said guide rails for at least one of said displaceable carriages.

16. (New) A baking oven, comprising:

- a baking chamber;

- a baking rack insertable in said baking chamber;

- a holding part, said holding part horizontally guided in said baking chamber;

- said holding part receiving and holding said baking rack;

- said holding part and said baking rack displaceable between a baking position with said baking rack inside said baking chamber and a removed position with said baking rack

located, at least in part, outside and in front of said baking chamber;

said holding part including two retaining elements arranged on opposite side walls of said baking chamber and at a distance from at least one of the top wall and the bottom wall of said baking chamber; and

each of said two retaining elements is guided by a displaceable carriage mounted on a guide rail, said guide rails affixed to said opposite side walls of said baking chamber.

17. (New) The baking oven according to claim 16, including each of said guide rails is affixed and each said displaceable carriage is arranged one of said opposite side walls of said baking chamber in a middle height region of said baking chamber.

18. (New) The baking oven according to claim 16, including each of said two retaining elements including a hooked rail which is affixed to one of said displaceable carriages, said hooked rail having a plurality of grooves for suspending a baking rack at a desired location from a pair of said grooves, one in each of said hooked rails.

19. (New) The baking oven according to claim 18, including said hooked rails are fixedly connected to one another by a cross bracing.

20. (New) The baking oven according to claim 16, including at least one of said displaceable carriages having a locating position at least in said removed position.

21. (New) The baking oven according to claim 16, including each of said displaceable carriages is roller-mounted on one of said guide rails.

22. (New) The baking oven according to claim 21, including each of said displaceable carriages is roller-mounted on one of said guide rails by at least one roller element above and below of said guide rail.

23. (New) The baking oven according to claim 22, including each of said displaceable carriages is roller-mounted on one of said guide rails by at least one roller element above and below of said guide rail and said roller element above said guide rail is offset laterally from said roller element below said guide rail.

24. (New) The baking oven according to claim 22, including each of said displaceable carriages is roller-mounted on one of said guide rails by at least a pair of roller elements above and a pair of roller elements below said guide rail.

25. (New) The baking oven according to claim 22, including a forward and a rear stop position on at least one of said guide rails for at least one of said displaceable carriages.

26. (New) The baking oven according to claim 16, including a forward and a rear stop position on at least one of said guide rails for at least one of said displaceable carriages.